

SPECIFIATIONS





Chamber capacity	0250xD350mm	
Inside Capacity	18 Liter	
Outside Size (L*W*H)CM	60*39*36	56*39*36
Packing Size (L*W*H)CM	61*53*40	61.5*44*36.5
	N.W:33KGS:G.W: 35KGS	N.W:27KGSG.W:28KGS
Sterilize Temerature	122°C &134°C	122°C & 134°C '
Sterilize Pressure (Mpa)	0.12Mpa & 0.23Mpa	0.12Mpa & 0.23Mpa
Sterilize Time	25Min & 6Min	25Min & 6Min
Dry Time	Immobile range is 40 min	No dry function
Hearter	1100W	900W
Material Quality	Stainless Steel SUS # 304. Boiler Chamber surface With burnish.	
Surface Deal With	The machine foundation and the shell use high temperature baking Vanish Processing	
Electrical Current-110V	10A	8A
Electrical Current-220V	5A	4A
Automatic Supply Water System	Yes	Manual give the water
Safety Equipment	*Pressure adjustment: adjust the inter pressur. If over standard Value	
e e	automatic vent.	
	* Avoid overheat protect device: When inter temperature overheat, power break electric Current automatically.	
Automatic Vent Water	Have the device	
-air adiustment	Trave the device	
Store Water Box (2000ml)	Have the device	No
Led lights indicate the level of	Have the device	No
Water tank		
Sterilize Frame	Standard accessories(Plate*3Pcs. Shelf*1Pcs, Take Plate tool*1Pc)	
-use stainless steel material	(Plate Size : L26*W18*H2 CM)	
Temperature and pressure display	LED Several Windows.	LED Several Windows.
Disinfection principle	Uses the hot vapor power	Uses the hot vapor power
	Emissions cold air / 2 time	emissions cold air /2 time

